

Jukeboxes for CD-ROM

TERASTORE CDR L



The **TERASTORE CDRL** is a high-quality, compact and low-priced storing system based on CD-ROM mediums. The fully equipped basic version disposes of 6 CD drives and 12 50-disc interchangeable magazines.

The integrated CD-ROM and CD-R drives allow using CD-ROM, CD-R and CD-RW mediums.

The single discs are loaded or unloaded through a mail slot or by the 50-disc interchangeable magazines. The menu-driven operation is uncomplicated. A display shows all relevant information.

An internal air filtration system prevents soiling of the discs.

The jukeboxes are equipped with a **LVD-SCSI-Interface** (Low Voltage Differential), which controls the data transfer between server and drives. The SCSI-Interface also transmits the control commands to the robotics.

The additional serial interface makes a diagnostic mode for local use or remote dial-up possible.

DSM

Handhabungssysteme
GmbH & Co. KG

The Partner of Professionals

Fully automatic handling of up to 600 discs at reasonable prices.

Jukebox

Drives
number

Disc
capacity

Storage
capacity GB max.

CDRL

2

600

390

CDRL

4

600

390

CDRL (max. drives)

6

600

390

Dimensions w / h / d in mm

777 / 1.640,6 / 807

Weight

106 kg (+/- 10%)

Operating temperature / humidity

+5°C to +35°C / 10% to 80%

Mains Voltage

230 V / 50 Hz / 1 A (115 V / 60 Hz)

Power consumption (max.)

100 W

Interface

LVD-SCSI (Low Voltage Differential)

Average disc load time in sec.

4

Applicable standards

CE, TÜV/GS, UL, CSA and FCC-B

MSBF (Mean Swaps Between Failures)

2.500.000

MTTR (Mean Time To Repair)

30 min

Accessories

NAJ - Version

Fibre Channel Interface

Headquarters

Zum Heerenberg 3
D - 26655 Westerstede
Tel.: +49 (0) 44 88 / 76 43 - 0
Fax: +49 (0) 44 88 / 76 43 - 21
eMail: dsm@terastore.de

Sales Office Karlsruhe

Haid- u. Neustraße 7-9
D - 76131 Karlsruhe
Tel.: +49 (0) 7 21 / 9 65 85 29
Fax: +49 (0) 7 21 / 60 63 08